



0673

Watertight fixture IP68 down to 20m













Description

Pressure watertight lighting fixtures are applicable for a wide range of different areas, mainly often submerged areas. They are designed to withstand high water pressure and to meet maritime requirements.

The polycarbonate cover tube of 4 mm thickness is able to resist heavy seas. Mounted with special clamps this fixture is the best solution to be mounted at the focsle. The 0673 is the next generation of 0273 with an enlarged terminal compartment.

Highlights:

Safe down to 20 meters water depth Removable gear tray for easy installation Wash resistant

Technical specifications

Lightsource/Optic

Designed for LED 15W covered by a clear polycarbonate cover tube of 4 mm thickness. The gear tray is made of zinc coated steel for the 18W and 36W version, for the LED version ismade fromaluminium.all gear trays are powder coated white to give a maximum light output.

Electrical specification

This fixture is available with magnetic or electronic ballast, fixed on a removable gear tray, the through wiring as option makes it easy to connect the fittings. Different cable glands in polyamide in M20 and M25 are available.

Mounting

mounted by 2 clamps (to be ordered separatly), see spare parts an accessories.

Diffuser

Clear polycarbonate cover tube of 4 mm thickness and polycarbonate end caps.

Cable entry

Polyamide gland M20 x 1.5 (cableø 6-12 mm) M25 x 1.5 (cableø 13 - 18 mm)

Termination

Plug connection 3-pole/2.5mm².





Finish

Powder coated white RAL9016 and enamelled up to 70 - 80 μm thickness.

Illustrations




















Images





