



TL60 LED

Innovative watertight LED luminaire















Description

The innovative LED outdoor lighting fixtures are applicable for a wide range of different areas, e.g. workshops, engine rooms, stores, passage ways etc. They are designed to meet maritime requirements and to save energy and maintenance cost due to extreme long lifetime.

The combination of material and design assures an excellent heat management and therefore a long lifetime.

Technical specifications

Application

For areas like car decks, open decks, engine rooms and other demanding applications such as extreme weather conditions at sea. Design: According to rules of maritime classification societies, additional VDE and IEC/EN

Remarks

ES = grounding with earth sheet ET = grounding with earth tag

Approvals

Germanischer Lloyd approved

Ambient temperature (Ta)

Operation from -35°C up to +55°C in standard version

Finish

Grey anodized

Connection

Connection box with cable entry 2xM25×1.5 polyamide D7-17mm and blind plugs 2xM25×1.5 polyamide Terminal 3-pole/6 mm²

Housing

Seawater resistant, anodized aluminium housing

Lightsource/Optic

Designed in two length with 2200 or 4500 lumen output from thefixture, Led's arecovered byopalic polycarbonate diffuser.






Electrical specification


High quality driver and high end Led's for a long lifetime, battery backup for emergency and dimmable versions are available.

Mounting

Mounted to the ceiling or cable trays by: screws, different screwed or welded mounting brackets, shock mounts or triangles are available.

Illustrations










Images



The Company reserves the right to change any product specifications without prior notification.







