



Construction : 6 x 24

Rope Diameter	Minimum Breaking Load (Metric Tons)			Approx. Weight (Kg/100m)
	Grade G (1470N/mm ²)	Grade A (1620N/mm ²)	Grade B (1770N/mm ²)	
8	2.98	3.21	3.50	21.20
9	3.77	4.06	4.43	26.90
10	4.65	5.02	5.47	33.20
11.2	5.83	6.30	6.87	42.28
12	6.70	7.23	7.88	47.80
12.5	7.29	7.85	8.55	52.09
14	9.12	9.48	10.7	65.10
16	11.9	12.8	14.0	80.36
18	15.1	16.3	17.7	108.0
20	18.6	20.1	21.9	133.0
22.4	23.3	25.2	27.5	167.0
24	26.8	28.9	31.5	191.0
25	29.1	31.4	34.2	205.4
28	36.5	39.3	42.9	260.4
30	41.9	45.2	49.3	299.0
31.5	46.3	49.9	54.4	316.4
33.5	52.4	56.4	61.5	373.0
35.5	58.8	63.3	69.1	399.6
37.5	65.7	70.7	77.1	467.0
40	74.4	80.3	87.6	532.0
42.5	84.3	90.8	98.9	600.0
45	94.5	102	111	672.0
47.5	105	113	124	749.0
50	116	125	137	821.5
52	126	136	148	898.0
54	136	146	160	968.0
56	146	157	172	1,040
58	156	169	184	1,116
60	167	181	197	1,200
63	185	199	217	1,320
63.5	188	202	221	1,340
74	255	275	300	1,819
76.2	270	291	318	1,929